

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

# EVERCOAT®

## 1. Identification

Product identifier used on the label:

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Other means of identification

Synonyms: No data available

Recommended use of the chemical and restrictions on use: Elimination of pin holes

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer /  
Importer / Distributor: ITW Evercoat  
a division of Illinois Tool Works Inc.  
6600 Cornell Road  
Cincinnati, OH 45242  
513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666

## 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard  
Symbols:



GHS Classification: Reproductive Toxicity Category 1B  
Skin Corrosion/Irritation Category 2  
Serious Eye Damage/Eye Irritation Category 2A  
Flammable Liquid Category 3  
Hazardous to the aquatic environment - Acute Category 3  
Hazardous to the aquatic environment - Chronic Category 3

GHS Signal Word: Danger

GHS Hazard Statements: Flammable liquid and vapour.  
Causes skin irritation.  
Causes serious eye irritation.  
May damage fertility or the unborn child.

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

## GHS Precautionary Statements:

### Safety Precautions:

Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Wash thoroughly after handling.  
Avoid release to the environment.

### First Aid Measures:

Wear protective gloves/protective clothing/eye protection/face protection.  
IF ON SKIN: Wash with plenty of soap and water.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.  
Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF exposed or concerned: Get medical advice/attention.  
Specific treatment (see on this label).  
If skin irritation occurs: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
In case of fire: Use appropriate media to extinguish.

### Storage:

Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

### Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

### Hazards not otherwise classified:

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

## 3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Xylene	1330-20-7	7 - 15
Ethylene glycol monobutyl ether	111-76-2	7 - 15
Methoxy 2-propyl Acetate	108-65-6	5 - 10
Ethyl Benzene	100-41-4	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

## 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Move individual away from exposure. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Wash affected area thoroughly with soap and water. Remove contaminated clothing and continue flushing with water. Wash clothing before reuse. Seek medical advice if symptoms persist

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Remove person to fresh air. Keep warm and quiet. If breathing is difficult, give oxygen by trained personnel. Seek immediate medical attention. Do not induce vomiting unless directed to do so by medical personnel. ASPIRATION HAZARD. This material may enter the lungs during vomiting. Never give anything by mouth to an unconscious person

**Most important symptoms/effects, acute and delayed:**

**Most important symptoms/effects (Acute):** No data available

**Most important symptoms/effects (Delayed):** No data available

**Indication of immediate medical attention and special treatment needed, if necessary:** No additional first aid information available

## 5. Fire-fighting measures

**Suitable (and unsuitable) extinguishing media:**

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

---

**Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical

**Unsuitable extinguishing media:** No data available

**Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):**

**Fire and/or Explosion Hazards:** Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

**Hazardous Combustion Products:** Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons

**Special protective equipment and precautions for fire-fighters:** Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

## 6. Accidental release measures

**Personal precautions, protective equipment, and emergency procedures:** Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

**Methods and materials for containment and cleaning up:** Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. All personnel in the area should be protected as in Section 8. Ensure adequate ventilation. Keep unnecessary and unprotected

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

personnel from entering the area. Prevent further leakage or spillage if safe to do so. Dike area to contain the spill and prevent releases to sewers, drains or other waterways. Do not allow the spilled product to enter public drainage system or open waterways. Prevent spilled material from contaminating soil, entering sanitary sewers, storm sewers, and drainage systems, and entering bodies of water or ditches that lead to waterways. Environmental precautions Prevent spreading over a wide area Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

## 7. Handling and storage

**Precautions for safe handling:** Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Gas, vapor, mist, or dust may be harmful if inhaled. Do not get in eyes, on skin and clothing Remove contaminated clothing and continue flushing with water. Wash clothing before reuse. Wash thoroughly after handling Ensure adequate ventilation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Do not smoke. Ground and bond containers when transferring material Use an appropriate properly fitted respirator if exposures exceed PEL/TLV values.

### Conditions for safe storage, including any incompatibilities

**Conditions for safe storage:** Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition Store in a tightly closed container Store in a cool dry place

**Materials to Avoid/Chemical Incompatibility:** Strong oxidizing agents Strong acids Strong alkalis Aldehydes Amines Halogenated compounds Isocyanates

## 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Xylene	100 ppm	100 ppm	150 ppm
Ethylene glycol monobutyl ether	50 ppm	20 ppm	No data available
Ethyl Benzene	100 ppm	100 ppm	No data available

**Appropriate engineering controls:** Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

overexposure. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

## Individual protection measures, such as personal protective equipment:

### Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to protect against the splash of product. An eye wash station must be available where this product is used.

### Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

### Respiratory Protection:

Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

### Other Protective Equipment:

Splash proof chemical goggles are recommended to protect against the splash of product. An eye wash station must be available where this product is used. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

## 9. Physical and chemical properties

### Appearance (physical state, color, etc.):

Appearance (physical state):	Paste
Color:	Grey
Odor:	No data available
Odor threshold:	No data available
pH:	No data available
Melting Point/Freezing Point (°C):	No data available
Initial Boiling Point and Boiling Range (°C):	139
Flash Point (°C):	27
Evaporation Rate:	No data available

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

---

Flammability (solid, gas):	No data available
Upper/lower flammability or explosive limits:	
Upper Flammable/Explosive Limit (%):	7
Lower Flammable/Explosive Limit (%):	1
Vapor Pressure:	No data available
Vapor Density:	No data available
Relative Density:	Not determined
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	1.36
Auto-ignition Temperature (°C):	No data available
Decomposition Temperature:	No data available
Viscosity:	No data available
VOC (as packaged-less exempts and water):	2.9 lbs/gal or 347 g/L
VHAP Content by weight – as packaged:	12 %

## 10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	No data available
Conditions to avoid (e.g., static discharge, shock, or vibration):	Sources of ignition hot surfaces Open flames
Incompatible materials:	Strong oxidizing agents Strong acids Strong alkalies Aldehydes Amines Halogenated compounds Isocyanates
Hazardous decomposition products:	Carbon dioxide Carbon monoxide

## 11. Toxicological information

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

---

**Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):** Skin contact, Ingestion, Eye contact, Absorption

**Symptoms related to the physical, chemical and toxicological characteristics:** No data available

**Delayed and immediate effects and also chronic effects from short- and long-term exposure:**

**Immediate (Acute) Health Effects by Route of Exposure:**

**Inhalation Irritation:** Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. At elevated temperatures may cause irritation of the eyes and respiratory tract

**Inhalation Toxicity:** Harmful! Can cause systemic damage (see "Target Organs")

**Skin Contact:** Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Skin Absorption:** Minimal hazard in normal industrial use. May cause gastrointestinal discomfort  
Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Substance can be absorbed through the skin in harmful amounts.

**Eye Contact:** Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible. Can cause irritation.

**Ingestion Irritation:** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Irritating to mouth, throat, and stomach. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.  
Ingestion is not an anticipated route of exposure for this material in industrial use.

**Ingestion Toxicity:** Harmful if swallowed. May cause systemic poisoning.

**Long-Term (Chronic) Health Effects:**

**Carcinogenicity:** None of the substances have been shown to cause cancer in long term animal studies. Not a carcinogen according to NTP, IARC, or OSHA. This material contains a chemical which is listed by the International Agency for Research on Cancer (IARC) as a group 2B cancer causing agent (possibly carcinogenic to humans).

**Reproductive and Developmental Toxicity:** May damage fertility or the unborn child.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

**Inhalation:** Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.  
Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")

**Skin Contact:** Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

**Skin Absorption:** Upon prolonged or repeated exposure, minimal hazard in normal industrial use.  
May cause gastrointestinal discomfort.



# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

## Numerical measures of toxicity (such as acute toxicity estimates)

### Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Xylene	Oral LD50 Rat 4300 mg/kg		Inhalation LC50 (4h) Rat 5000 ppm
Ethylene glycol monobutyl ether	Oral LD50 Rat 470 mg/kg		Inhalation LC50 (4h) Rat 2900 mg/m3

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available	N	N	N

## 12. Ecological information

<b>Ecotoxicity (aquatic and terrestrial, where available):</b>	Toxic to aquatic life with long lasting effects. Toxic to aquatic life. Harmful to aquatic life. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.
<b>Persistence and degradability:</b>	No data available
<b>Bioaccumulative potential:</b>	No data
<b>Mobility in soil:</b>	No data available
<b>Other adverse effects (such as hazardous to the ozone layer):</b>	No data available

### Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Xylene			Aquatic LC50 (96h) 7.711 - 9.591 MG/L

## 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

<b>Description of waste residues:</b>	Spent or discarded material is a hazardous waste.
<b>Safe Handling of Waste:</b>	Disposal must be in accordance with applicable Federal, State/Provincial and Local regulations.
<b>Waste treatment methods (including packaging):</b>	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
<b>Waste Disposal Code(s):</b>	D001

# Safety Data Sheet

Product Name: 440EXPRESS, 16 FL.OZ.

Product identifier: 100440

Revision Date: 10-21-2016

Replaces:

## 14. Transport information

UN number: UN1263  
UN proper shipping name: Paint  
Transport hazard class(es): 3  
Packing group: III

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

## 15. Regulatory information

**Safety, health and environmental regulations specific for the product in question**

TSCA Status: The intentional ingredients of this product are listed.

### Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Xylene	1330-20-7	N	N	Y	N
Ethyl Benzene	100-41-4	N	N	N	Y
p-Xylene	106-42-3	N	N	Y	N
Benzene	71-43-2	N	N	Y	Y

## 16. Other information, including date of preparation or last revision.

Revision Date: 10-21-2016  
Revision Number: 10

**Disclaimer:** NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances