

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

EVERCOAT®

1. Identification

Product identifier used on the label:

Product Name: Durabuild Gray

Product identifier: 102274

Other means of identification

Synonyms: No data available

Recommended use of the chemical and restrictions on use: Acrylic Primer Surfacer

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer /
Importer / Distributor: ITW Evercoat
a division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, OH 45242
513-489-7600

Emergency phone number: CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard
Symbols:



GHS Classification: Serious Eye Damage/Eye Irritation Category 1
Flammable Liquid Category 2
Skin Corrosion/Irritation Category 2
Carcinogenicity Category 2
Reproductive Toxicity Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2
Hazardous to the aquatic environment - Acute Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

GHS Signal Word: Danger

GHS Hazard Statements: Highly flammable liquid and vapour.
Causes skin irritation.

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

Causes serious eye damage.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Toxic to aquatic life.

GHS Precautionary Statements:

Safety Precautions:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapours/spray.
Avoid breathing dust/fume/gas/mist/vapours/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures:

IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Immediately call a POISON CENTER/doctor
Call a POISON CENTER or doctor/physician if you feel unwell.
Get medical advice/attention if you feel unwell.
Specific treatment (see on this label).
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.

Storage:

In case of fire: Use appropriate media to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise classified:

No data available

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Toluene	108-88-3	10 - 30
n-Butyl acetate	123-86-4	7 - 15
2-Propanol	67-63-0	1 - 5
Titanium dioxide	13463-67-7	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

- Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel.
- Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
- Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately
- Ingestion:** Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this MSDS. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

Most important symptoms/effects, acute and delayed:

Most important symptoms/effects (Acute): No data available

Most important symptoms/effects (Delayed): No data available

Indication of immediate medical attention and special treatment needed, if necessary: No additional first aid information available

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire.

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Hazardous Combustion Products: Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-fighters: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Flammable component(s) of this material may be lighter than water and burn while floating on the surface.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up: Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

7. Handling and storage

Precautions for safe handling: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Use spark-proof tools and explosion-proof equipment

Conditions for safe storage, including any incompatibilities

Conditions for safe storage: Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from sources of ignition

Materials to Avoid/Chemical Incompatibility: Strong oxidizing agents Strong alkalies Strong acids Metals

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Toluene	100 ppm	100 ppm	No data available
n-Butyl acetate	150 ppm	150 ppm	200 ppm STEL; 950 mg/m ³ STEL
Titanium dioxide	15 mg/m ³	10 mg/m ³	No data available

Appropriate engineering controls: No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Individual protection measures, such as personal protective equipment:

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Wear splash-proof safety goggles if material could be misted or splashed into eyes. Wear goggles if dusts can reach the exposure limit.

Skin Protection: Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Respiratory Protection: Respiratory protection may be required to avoid overexposure

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator. Respiratory protection may be required in addition to ventilation depending upon conditions of use. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres

Other Protective Equipment: Wear splash-proof safety goggles if material could be misted or splashed into eyes. Wear goggles if dusts can reach the exposure limit.

9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state):

Liquid

Color:

Grey

Odor:

Strong

Odor threshold:

No data available

pH:

7

Melting Point/Freezing Point (°C):

No data available

Initial Boiling Point and Boiling Range (°C):

111

Flash Point (°C):

6

Evaporation Rate:

No data available

Flammability (solid, gas):

No data available

Upper/lower flammability or explosive limits:

Upper Flammable/Explosive Limit (%):

7.0 %

7.6 %

Lower Flammable/Explosive Limit (%):

1.0%

Vapor Pressure:

No data available

Vapor Density:

No data available

Relative Density:

1.26

Solubility(ies):

Insoluble

Partition coefficient: n-octanol/water:

1.36

Auto-ignition Temperature (°C):

No data available

Decomposition Temperature:

No data available

Viscosity:

1200

VOC (as packaged-less exempts and water):

4.46 lbs/gal or

VOC (as applied*- 2% by wt hardener- less exempts and water):

4.27 lbs/gal or

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	No data available
Conditions to avoid (e.g., static discharge, shock, or vibration):	Contamination
Incompatible materials:	Strong oxidizing agents Strong alkalies Strong acids Metals

11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Inhalation, Skin contact, Eye contact, Absorption, Ingestion, Skin contact, Eye contact
Symptoms related to the physical, chemical and toxicological characteristics:	No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Can cause mechanical irritation if dusts are generated.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	Harmful if absorbed through the skin. May cause severe irritation and systemic damage.
Eye Contact:	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible. Can cause mechanical irritation if dusts are generated.
Ingestion Irritation:	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.

Long-Term (Chronic) Health Effects:

Carcinogenicity:	Suspected of causing cancer.
Reproductive and Developmental Toxicity:	Suspected of damaging fertility or the unborn child.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Inhalation:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Upon prolonged

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")

Skin Contact:

Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Skin Absorption:

Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Numerical measures of toxicity (such as acute toxicity estimates)

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	Oral LD50 Rat 5000 mg/kg		Inhalation LC50 (4h) Rat 4000 ppm
n-Butyl acetate	Oral LD50 Rat 13100 mg/kg		Inhalation LC50 (4h) Rat 2000 ppm

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Titanium dioxide	N	Y	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):
Persistence and degradability:
Bioaccumulative potential:
Mobility in soil:
Other adverse effects (such as hazardous to the ozone layer):

Toxic to aquatic life. Harmful to aquatic life. Components of this product are hazardous to wildlife and aquatic life.
 No data available
 No data
 No data available
 No data available

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
n-Butyl acetate			Aquatic LC50 (96h) 17 - 19 MG/L
Titanium dioxide	Aquatic EC50 (48h) Daphnia > 1000 ml/l		Aquatic LC50 (96h) > 1000 MG/L

Safety Data Sheet

Product Name: Durabuild Gray

Product identifier: 102274

Revision Date: 12-19-2016

Replaces:

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Description of waste residues: Spent or discarded material is a hazardous waste.

Waste treatment methods (including packaging): Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste Disposal Code(s): D001

14. Transport information

UN number: UN1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: II

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

TSCA Status: All components in this product are on the TSCA Inventory.

Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Toluene	108-88-3	N	N	Y	Y
Titanium dioxide	13463-67-7	N	N	Y	Y
Carbon black	1333-86-4	N	N	N	Y

16. Other information, including date of preparation or last revision.

Revision Date: 12-19-2016

Revision Number: 13

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances