EVERCOAT®

PREMIUM PAINT FINISHING

Four Products. One System.

EVERCOAT®

EVERCOAT®

PREMIUM PAINT FINISHING SYSTEM

FOUR PRODUCTS. ONE SYSTEM.

The Evercoat Premium Paint Finishing system is a technically advanced system for refinishing professionals. These high-quality products provide the user with time-saving applications and deliver a durable and exceptional high-gloss finish, producing a true "show car shine" every time!

All products in the Premium Paint Finishing system are …

- Water soluble for quick and easy clean-up
- Safe for use on all paint finishes
- Body shop safe

TRIPLE CUT COMPOUND

- Easily removes 1200 grit and finer sand scratches and produces a low swirl finish
- Unique multi-phase abrasive breaks down during use providing a high-gloss, haze-free surface

Part No.	Size	Units Per Case
100019	QUART	12

TRIPLE GLAZE

- Specially formulated to remove 3000 to 4000 grit wet sand scratches and compound swirl marks
- Produces a high-gloss, swirl-free finish

Part No.	Size	Units Per Case
100030	QUART	6

TRIPLE GLOSS

- Removes micro-fine scratches and provides paint protection with exceptional gloss
- Easy-to-use finishing glaze formulated to achieve the ultimate wet look finish
- Works great on dark colors

Part No.	Size	Units Per Case
100032	QUART	6

TRIPLE MIST

- Exceptional for final wipe down to achieve a brilliant show car appearance.
- Quickly removes smudges, fingerprints, compound dust and other finishing residues
- Excellent lubricant for Clay Magic®

Part No.	Size	Units Per Case
100035	22 fl oz. SPRAYER	12

STEP 1

- Apply sparingly to a 2' x 2' area
- Buff with a wool pad, or foam compounding pad at 1400 – 1800 rpm

(For light colors use a medium foam pad to eliminate swirl marks and enhance gloss)

TIP: To enhance the workability of Triple Cut Compound, spray a small amount of water onto surface or pad before buffing.

STEP 2

- Apply sparingly to a 2' x 2' area
- Buff with a medium foam polishing pad at 1400 – 1800 rpm

(For removal of swirl marks, use medium pressure, or use light pressure for polishing)

TIP: For light colors, use a fine foam polishing pad at 1200 – 1400 rpm as a final step.

STEP 3

- Apply sparingly to a 2' x 2' area
- Use an Ultra Fine Foam Polishing Pad at 1400 – 1600 rpm

(To eliminate fine swirl marks use medium pressure followed by light pressure to enhance gloss)

TIP: Can be used as a hand glaze.

STEP 4 (OPTIONAL)

- Shake lightly
- Apply sparingly onto a cool dry surface 2' x 2' at a time
- Working evenly, use a clean microfiber towel
- Hand buff to a high gloss finish

EVERCOAT®

PREMIUM PAINT FINISHING SYSTEM

EVERCOAT®	SAND SCRATCH REMOVAL (1200 or Finer Grit)	COMPOUND SWIRLS AND HAZE	FINE SWIRL MARKS AND SCRATCHES	COMPOUND AND POLISH RESIDUE
019 **TRIPLE CUT COMPOUND** Apply a small amount to work a 2'x2' area.	WOOL PAD	MEDIUM FOAM PAD		
030 **TRIPLE GLAZE** Apply a small amount to area being polished		MEDIUM FOAM PAD	FINE FOAM PAD	
032 **TRIPLE GLOSS** Apply a small amount to area being polished			ULTRA FINE FOAM PAD (DARK COLORS)	HIGH QUALITY MICROFIBER TOWEL (APPLY BY HAND)
035 **TRIPLE MIST** Lightly mist entire area				HIGH QUALITY MICROFIBER TOWEL

EVERCOAT®
a division of Illinois Tool Works Inc. | 6600 Cornell Road | Cincinnati, OH 45242 | 1-513-489-7600
Made and Printed in the U.S. | ©2009 Evercoat
evercoat.com

704119 (4/09)

EVERCOAT®