

PRODUCT: MEDIUM DUTY RUBBING COMPOUND

PART NUMBER: 100023 Quart 12 units/case
100024 Gallon 4 units/case

DESCRIPTION: MEDIUM DUTY RUBBING COMPOUND is a creamy, tan-colored compound formula for removing heavy compound scratches, surface oxidation, orange peel, wet sanding marks, and moderate topcoat imperfections. Rinses quickly and easily from jambs moldings, and emblems. Excellent for all types of paint finishes. "Air dried, baked, or Infra-red" Contains no silicone or waxes. Body shop safe.

USES: Repair and removal and of topcoat imperfections on fresh or cured paint:
Orange Peel Dirt nibs
Oxidation Sand Marks

APPROVED FINISHES:

- Lacquer Topcoats
- Acrylic Enamel Topcoats
- Basecoat /Clearcoat Systems
- Acrylic Urethane Topcoats

All paint coatings are different in their drying and curing characteristics based on their chemistry, drying mechanism, (air dry vs. bake), and environmental conditions. It is important that proper sanding and buffing times (based on the type of coating) are followed according to the paint manufacturer's recommendations.

PREPARATION: Identify severity of topcoat imperfection and choose sand paper grit accordingly (i.e. dirt nibs 1,500 grit). After sanding wipe area to remove sanding residue. Clean buffing pad occasionally before and during use with a cleaning spur tool.

APPLICATION: Shake product well before using. Apply product sparingly, enough to work a two foot square area, onto the sanded area. Spread product with buffing pad and begin buffing with light to moderate pressure at approximately 1750 rpm. Continue buffing until sand marks are removed.

Inspect repair area for sand marks. In some cases all marks are not removed due to buffing techniques, therefore a second application maybe necessary.

Note: If product begins to dry or additional buffing is needed, mist LUBRI-SHINE™ onto the surface to reactivate the product.

FINISH: Wipe down surface with a soft, clean, dry cloth to remove residue and dust.

TECHNICAL SPECIFICATIONS:

- | | |
|------------------------|---|
| • Appearance | Tan creamy liquid |
| • VOC | Refer to Section 9 of the Safety Data Sheet |
| • Residue clean-up | Excellent |
| • Water Soluble | Yes |
| • Maximum sanding grit | 1,200 grit wet, 1,500 grit dry DA |
| • Scent | Solvent |

SAFETY & HANDLING: Read all directions and warnings prior to using Evercoat products. Safety Data Sheets can be found online at www.evercoat.com.

CAUTION: Keep product from freezing.