


PRODUCT: KITTY HAIR® Long Strand Fiberglass Reinforced Filler

PART NUMBER: 100868 Quart 6 units/case
100869 Gallon 4 units/case

DESCRIPTION: Best known for its bridging capabilities in rebuilding shattered fiberglass and reinforcing torn or rusted areas of sheet metal, KITTY HAIR® is formulated with long strands of chopped fiberglass which doubles the strength of standard fillers. Waterproof and rustproof, KITTY HAIR® can be applied without fiberglass mat or cloth.

APPROVED SUBSTRATES:




- Steel
- Galvanized Steel
- Aluminum
- SMC
- Fiberglass
- Most Rigid Plastics

PREPARATION:



- Clean and degrease the entire panel to be repaired with soap and water, followed by a mild cleaning solvent to remove oil, grease, and wax. Surface must be thoroughly dry before repairing or applying material.
- Keep the repair area small. Use 40-80 grit to remove the paint and featheredge.

MIXING:



- Mix the product before using. Knead the cream hardener.
- Measure hardener 2% by weight (add a ribbon of cream hardener from edge to edge across the center of a 4" diameter puddle).
- Puddles larger than 4" (10 cm) in diameter will require additional hardener. Mix thoroughly until uniform color is achieved.
- Approximate setting time is 10-15 minutes @ 72°F-80°F (22°C)

APPLICATION:



- Apply in layers with even firm pressure to force into repair area.
- Do not apply all at once.

FINISH:



- Sand filler with 80 grit sandpaper.
- Apply a finish coat of any Evercoat lightweight body filler or polyester putty.

TECHNICAL SPECIFICATIONS:

- | | |
|--------------------------------------|---|
| ▪ Appearance | Long strand fibrous paste |
| ▪ VOC | Refer to Section 9 of the Safety Data Sheet |
| ▪ Relative Density | Refer to Section 9 of the Safety Data Sheet |
| ▪ Sand Time | 20 - 25 min. |
| ▪ Max Recommended Thickness (sanded) | ½ inch (12 mm) |

NOTE: Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat® products. Safety Data Sheets can be found online at evercoat.com.

NOTES:

Never return mixed filler to can

Keep can closed and store in a cool dry place

USE WITH CREAM HARDENER ONLY!