

PRODUCT: Maxim™ Panel Prep

PART NUMBER: 100881 Aerosol (9.5 Oz.) 12 units/case

DESCRIPTION: Maxim™ Panel Prep is formulated to remove solvent and water based surface contaminants from plastic parts prior to the repair process. Easy wipe on application with a clean cloth and wipe off. Fast drying with no residue. Can be used with epoxy and urethane repair products. Removes mold release on plastics. Enhances the adhesion of repair materials and topcoats.

APPROVED SUBSTRATES:

- All topcoats

CLEANING:

- Clean part with soap and water. Allow to dry thoroughly.
- Use a clean, dry cloth to wipe the area dry

APPLICATION:

- Apply to a clean, lint-free cloth and wipe surface
- Wipe from center of repair area to outside edge.
- Wipe dry with a clean, dry, lint-free cloth.

TECHNICAL SPECIFICATIONS:

- | | |
|-----------------|---|
| ▪ Appearance | Clear, watery liquid |
| ▪ VOC | Refer to Section 9 of the Safety Data Sheet |
| ▪ Water Soluble | Yes |
| ▪ Odor | N/A |

NOTE: Physical testing performed at approximately 72°F (22°C) / 75% RH unless otherwise noted

SAFETY & HANDLING:

For professional use only, read all directions and warnings prior to using Evercoat® products. Keep cartridge closed and store in a cool dry place.

Safety Data Sheets can be found online at evercoat.com.



a division of Illinois Tool Works Inc. | 6600 Cornell Road | Cincinnati, OH 45242 | (513) 489-7600
Made and Printed in the U.S. | ©2015 Evercoat

evercoat.com

100-310-100881-TDS

2.2015