

PRODUCT: Maxim™ Adhesion Promoter

PART NUMBER: 100883 Aerosol (8 Oz.) 12 units/case

DESCRIPTION: Maxim™ Adhesion Promoter is a blend of resins formulated to create a chemical bond to enhance the adhesion of plastic repair fillers and paint coatings to flexible and semi-rigid plastics. Can be used with epoxy and urethane repair products. Adhesion Promoter is also an excellent tie-coat sealer applied to raw flexible and semi-rigid plastics including TPO and TPE. Can be used on OEM and aftermarket plastic parts.

PREPARATION: Surface must be cleaned according to directions for Panel Prep before applying Adhesion Promoter.

- APPLICATION:**
- Shake can before applying.
 - Apply a light to medium coat from a distance of 10-12 inches.
 - Allow to dry thoroughly.
 - Apply repair filler, primer or topcoats.

NOTE: Not to be used on fiber reinforced plastic. Adhesion promoter must be completely dry before applying repair filler or topcoats.

TECHNICAL SPECIFICATIONS:

▪ Appearance	Hazy pale yellow liquid
▪ VOC	Refer to Section 9 of the Safety Data Sheet
▪ Water Soluble	No
▪ Odor	Aromatic

NOTE: Physical testing performed at approximately 72°F (22°C) / 75% RH unless otherwise noted

SAFETY & HANDLING:

For professional use only, read all directions and warnings prior to using Evercoat® products. Keep cartridge closed and store in a cool dry place. Safety Data Sheets can be found online at evercoat.com.