


PRODUCT: TIGER HAIR® Long Strand Fiber Reinforced Filler

PART NUMBER: 101189 Quart 6 units/case
101190 Gallon 4 units/case

DESCRIPTION: The original long fiber, fiberglass reinforced filler; TIGER HAIR® is extra high strength. TIGER HAIR® can be used without fiberglass mat or cloth. It's ideal for heavy duty damage and bulk filling rust repairs. Can be used to repair SMC, fiberglass, rigid plastic, steel, galvanized steel and aluminum.

APPROVED SUBSTRATES:




- Steel
- Galvanized Steel
- Aluminum
- SMC
- Fiberglass
- Most Rigid Plastics

PREPARATION:



- Clean and degrease the entire panel to be repaired with soap and water, followed by a mild cleaning solvent to remove oil, grease, and wax. Surface must be thoroughly dry before repairing or applying material.
- Keep the repair area small. Use 40-80 grit to remove the paint and featheredge.

MIXING:



- Mix the product before using. Knead the cream hardener.
- Measure hardener 2% by weight (add a ribbon of cream hardener from edge to edge across the center of a 4" diameter puddle).
- Puddles larger than 4" (10 cm) in diameter will require additional hardener. Mix thoroughly until uniform color is achieved.
- Approximate setting time is 6-10 minutes @ 72°F-80°F (22°C)

APPLICATION:



- Apply in layers with even firm pressure to force into repair area.
- Do not apply all at once.

FINISH:



- Sand filler with 80 grit sandpaper.
- Apply a finish coat of any Evercoat lightweight body filler or polyester putty.

TECHNICAL SPECIFICATIONS:

- | | |
|--------------------------------------|---|
| ▪ Appearance | Long strand fibrous paste |
| ▪ VOC | Refer to Section 9 of the Safety Data Sheet |
| ▪ Relative Density | Refer to Section 9 of the Safety Data Sheet |
| ▪ Sand Time | 20 - 25 min. |
| ▪ Max Recommended Thickness (sanded) | ½ inch (12mm) |

NOTE: Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat® products. Safety Data Sheets can be found online at evercoat.com.

NOTES:

Never return mixed filler to can

Keep can closed and store in a cool dry place

USE WITH CREAM HARDENER ONLY!