

SAFETY DATA SHEET

Medium Adhesive - Urethane (104185)

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name and/or code : Medium Adhesive - Urethane (104185)**Manufacturer** : Evercoat
a Division of Illinois Tool Works Inc.
6600 Cornell Road
Cincinnati, Ohio USA
Phone: 1-513-489-7600**e-mail address of person responsible for this SDS** : marketing@evercoat.com**Emergency telephone number (with hours of operation)** : CHEMTEL, INC: 1-800-255-3924**Product use** : Medium Urethane Adhesive

2. HAZARDS IDENTIFICATION

The product is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Xi; R36/37/38
R42/43**Human health hazards** : Irritating to eyes, respiratory system and skin. May cause sensitisation by inhalation and skin contact.**Additional warning phrases** : Contains isocyanates. See information supplied by the manufacturer. This information is provided by the present Safety Data Sheet.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name	CAS number	%	EC number	Classification
4,4' Diphenylmethane Diisocyanate	101-68-8	50 - 100		Xi; R36/37/38 [1] R42/43
Diphenylmethane Diisocyanate	26447-40-5	5 - 12.5		R42 [1]
See section 16 for the full text of the R-phrases declared above				

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

4. FIRST AID MEASURES

First-aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.**Date of issue/Date of revision** : 4/16/2008.

Page: 1/6

4. FIRST AID MEASURES

- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray or mist.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Place in a suitable container. The contaminated area should be cleaned immediately with a suitable decontaminant. One possible (flammable) decontaminant comprises (by volume): water (45 parts), ethanol or isopropyl alcohol (50 parts) and concentrated (d: 0,880) ammonia solution (5 parts). A non-flammable alternative is sodium carbonate (5 parts) and water (95 parts). Add the same decontaminant to the remnants and let stand for several days until no further reaction in an unsealed container. Once this stage is reached, close container and dispose of according to local regulations (see section 13). Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. HANDLING AND STORAGE

Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

- Handling** : Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.

In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.

To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.

Keep container tightly closed. Precautions should be taken to minimise exposure to atmospheric humidity or water. CO₂ will be formed, which, in closed containers, could result in pressurisation. Care should be taken when re-opening partly-used containers. Keep away from heat, sparks and flame. No sparking tools should be used.

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

7. HANDLING AND STORAGE

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

Storage

: Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from heat and direct sunlight.

Keep away from: oxidising agents, strong alkalis, strong acids, amines, alcohols, water.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Do not empty into drains.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Examination of lung function should be carried out on a regular basis on persons spraying this preparation.

Engineering measures : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. In other operations, if local exhaust ventilation and good general extraction are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn. (See Personal protection.)

Occupational exposure limits : Not available.

Personal protective equipment

Respiratory system : By spraying: air-fed respirator.
By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask.

Skin and body : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Hands

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid.
Colour	: Beige.
Flash point	: Open cup: >200°C (>392°F)
Relative density	: 1.32
Vapour density	: 8.5 [Air = 1]

9. PHYSICAL AND CHEMICAL PROPERTIES

Solubility : Insoluble in the following materials: cold water and hot water.

10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: smoke, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids, amines, alcohols, water.

Uncontrolled exothermic reactions occur with amines and alcohols.

The product reacts slowly with water, resulting in the production of carbon dioxide. In closed containers, pressure build-up could result in distortion, expansion and, in extreme cases, bursting of the container.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Aquatic ecotoxicity

Conclusion/Summary : Not available.

Biodegradability

Conclusion/Summary : Not available.

13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses. Residues in empty containers should be neutralised with a decontaminant (see section 6).

Dispose of according to all federal, state and local applicable regulations.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

14. TRANSPORT INFORMATION

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Land - road/railway

Transport document name : -
Packing group : -

Sea

Proper shipping name : -
Special provisions : Not available.
Packing group : -
Marine pollutant : No.

Air

Proper shipping name : -
Special provisions : Not available.
Packing group : -

The "viscosity exemption" provisions do not apply to air transport.

Inland waterways

Proper shipping name : -
Packing group : -

This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.

15. REGULATORY INFORMATION

EU regulations : The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:

Hazard symbol or symbols :



Harmful

Risk phrases : R36/37/38- Irritating to eyes, respiratory system and skin.
R42/43- May cause sensitisation by inhalation and skin contact.

Safety phrases : S23- Do not breathe vapour or spray.
S24- Avoid contact with skin.
S37- Wear suitable gloves.
S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Contains : 4,4' Diphenylmethane Diisocyanate
Diphenylmethane Diisocyanate

Europe inventory : **Europe inventory:** All components are listed or exempted.

Additional warning phrases : Contains isocyanates. See information supplied by the manufacturer. This information is provided by the present Safety Data Sheet.

Industrial use : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

16. OTHER INFORMATION

CEPE Classification : 5

Full text of R-phrases referred to in sections 2 and 3 - Europe : R36/37/38- Irritating to eyes, respiratory system and skin.
R42- May cause sensitisation by inhalation.
R42/43- May cause sensitisation by inhalation and skin contact.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

Date of issue/Date of revision : 4/16/2008.

Version : 1.1

✔ Indicates information that has changed from previously issued version.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.