

PRODUCT: MEDIUM DUTY RUBBING COMPOUND

PART

NUMBER:	100023	Quart	12 units/case	31 lbs/case
	100024	Gallon	4 units/case	40 lbs/case

DESCRIPTION: MEDIUM DUTY RUBBING COMPOUND is a creamy, tan-colored compound formulated to remove heavy compound scratches, surface oxidation, orange peel, wet sanding marks and moderate topcoat imperfections. Rinses quickly and easily from jams, moldings, and emblems. Excellent for all types of paint finishes. "Air dried, Baked or Infra-red." Contains no silicones or waxes. Body Shop Safe.

FEATURES & ADVANTAGES:

This multi-functional compound can be used in paint refinishing and/or detailing of older paints. For example: scratch and oxidation.

The formula contains an abrasive package that shaves more than cuts through sanding marks and topcoat imperfections producing a cleaner clear finish.

This compound is designed to work excellent with wool or foam pads.

A versatile product in any paint finishing system.

Excellent on fresh paint.

USES: Repair and removal of paint imperfections on fresh or cured paints.

- Orange Peel
- Sand Scratches
- Oxidation

APPROVED PAINT FINISHES:

- Lacquer Topcoats
- Acrylic Enamel Topcoats—Properly Cured
- Acrylic Urethane Topcoats—Properly Cured
- Basecoat / Clearcoat Systems—Properly Cured

PREPARATION: Identify severity of topcoat imperfection and choose sandpaper grit accordingly (i.e. dirt nibs 1,500 grit). After sanding wipe area to remove residue from sanding. Thoroughly clean wool buffing pad by "spurring".

APPLICATION: Shake product well before using. Apply product sparingly, enough to work a two foot square area, onto the repair area. Spread product with wool pad and begin buffing with light to moderate pressure at 1750 rpm's. Continue buffing until sand marks are removed.

Inspect repair area for sand marks, in some cases all marks are not removed due to buffing technique; a second application maybe necessary.

Note: If product begins to dry or additional buffing is needed, mist LUBRI-SHINE® onto finish to reactivate the product.

MEDIUM DUTY RUBBING COMPOUND
PAGE 2

FINISH: Wipe down surface with a soft, clean, dry to remove residue and dust.

TECHNICAL

SPECIFICATIONS:

▪ Appearance	Tan creamy liquid
▪ VOC	-----
▪ Viscosity	-----
▪ Residue clean-up	Excellent
▪ Water Soluble	Yes
▪ Max Recommended sanding grit removal	1,500 grit wet, 1,500 dry DA
▪ Contents and Caution	MSDS available upon request

SAFETY &

HANDLING:

Read all directions and warnings prior to using Evercoat® products. Material Safety Data Sheets can be found online at www.evercoat.com.

CAUTION:

Keep product from freezing.

EVERCOAT®

a division of Illinois Tool Works Inc.
6600 Cornell Road • Cincinnati, OH 45242
(513) 489-7600 Fax (513)489-9229

evercoat.com

Made and Printed in the USA

© 2008 Evercoat

450-MDC-PIS