

**PRODUCT:** MACHINE GLAZE

**PART**

**NUMBER:** 100038      Quart      12 units/case      29 lbs/case

**DESCRIPTION:** A white, low-dusting aggressive machine glaze. Quickly eliminates compound swirls and scratches, wet sanding marks and light oxidation. Can be applied with a wool or foam pad. Rinses quickly and easily from jambs, moldings, and emblems. Excellent for all types of paint finishes. " Air dried, Baked or Infra-red." Body Shop safe. Contains no silicones or waxes.

**FEATURES &**

**ADVANTAGES:** Removes 2000 – 4000 grit sand scratches

Can be applied with a wool or foam compounding pad or foam polishing pad

Removes scratches and swirls instead of filling; contains no fillers

Leaves minimal residue; easily removed with soft cloth

Micro-thix formula minimizes "pad sling"

Excellent on fresh paint.

**USES:** Repair and removal of paint imperfections on fresh or cured paints.

**Example:** sanding marks, swirl marks, oxidation and light scratches

**APPROVED**

**PAINT FINISHES:** All type paints and curing methods.

**PREPARATION:** Blow off area with compressed air. Wipe area with soft cloth.

**APPLICATION:** Apply product sparingly, enough to work a two foot square area, onto the repair area.

Spread product with pad and begin buffing with light to moderate pressure at 1500 to 1750 rpm's.

Continue buffing until sand marks are removed.

**FINISH:** Wipe down surface with soft, clean, dry cloth to remover residue and dust.

**TECHNICAL SPECIFICATIONS:**

▪ Appearance	White creamy liquid
▪ VOC	-----
▪ Viscosity	-----
▪ Residue clean-up	Excellent
▪ Water Soluble	Yes
▪ Max Recommended sanding grit removal	2000-4000
▪ Contents and Caution	MSDS available upon request

**MACHINE GLAZE**  
**PAGE 2**

**SAFETY &  
HANDLING:**

Read all directions and warnings prior to using Evercoat® products. Material Safety Data Sheets can be found online at [www.evercoat.com](http://www.evercoat.com).

**NOTES:**

Always shake product before using

Inspect repair area for sand marks, in some cases all marks are not removed due to buffing pad and buffing technique; a second application maybe necessary.

**EVERCOAT®**

a division of Illinois Tool Works Inc.  
6600 Cornell Road • Cincinnati, OH 45242  
(513) 489-7600 Fax (513)489-9229  
evercoat.com  
Made and Printed in the USA  
© 2008 Evercoat

**450-MG-PIS**