

EVERCOAT®

EZ LITE COMMERCIAL

LIGHTWEIGHT BODY FILLER

Specially formulated to allow for a deep filling with excellent vertical hang, EZ Lite Commercial gives you 7 to 9 minutes of working time at 72°F (22°C). Perfect for mixing and spreading large quantities with confidence for larger surfaces, reducing the number of mixes to save you time and increase productivity.

Great for:

Steel, Galvanized Steel, Aluminum, Fiberglass, Stainless Steel, SMC



- ▶ Micro-Weight™ Light Weight Formula
- ▶ Extended Work Time
- ▶ Exceptional Vertical Hold
- ▶ Super Easy Sanding and Smooth Spreading

Applications

- ▶ Steel
- ▶ Aluminum
- ▶ Galvanized Steel
- ▶ Fiberglass
- ▶ Stainless Steel
- ▶ SMC

Benefits

May be mixed with Evercoat Rage Ultra Xtra (100145) to extend working time.

Evercoat Cream Hardener included

Technical Specifications

Part #	100287
Appearance	Off White Paste
Work Time	7 - 9 min. @ 72°F (22°C)
Sand Time	25 - 30 min.
Max Recommended Thickness	1/4 inch (6mm)
Package Size	1 gallon
Units/Case	4

Directions

Clean and degrease the entire panel to be repaired with soap and water, followed by a mild cleaning solvent. Thoroughly dry the surface before repairing. Keep the repair area small. Use 80 grit sandpaper to remove the paint and featheredge with 180.

Stir the filler before using. Knead the cream hardener. Measure hardener 2% by weight (add a ribbon of cream hardener from edge to edge across the center of a 4" diameter puddle). Puddles larger than 4" (10 cm) in diameter will require additional hardener. Mix thoroughly until uniform color is achieved.

Apply in layers with even firm pressure. Do not apply all at once.

Sand with 80-180 grit sandpaper. If necessary, reapply to fill any pinholes or low spots, allow filler to dry and then sand with 180 grit sandpaper. Finish sand with 180 grit or finer



Safety Data Sheet can be found on
Evercoat.com