


**PRODUCT:** HIGH PRODUCTION LITE WEIGHT® Plastic Body Filler

**PART NUMBER:** 100151      **Gallon**      **4 units/case**

**DESCRIPTION:** A smooth spreading, easy sanding auto body filler designed to sand to a fine finish.

**APPROVED SUBSTRATES:**



- Cold Rolled Steel
- Fiberglass


**NOTE:** For structural repairs prone to high degrees of stress and flexibility, use a fiber reinforced filler such as Everglass®, Kitty Hair® or Fiber Tech®.

**PREPARATION:**



- Clean and degrease the entire panel to be repaired with soap and water, followed by a mild cleaning solvent. Surface must be thoroughly dry before repairing or applying material.
- Keep the repair area small. Use 40-80 grit to remove the paint and featheredge.

**MIXING:**



- Stir the filler before using. Knead the cream hardener.
- Measure hardener 2% by weight (add a ribbon of cream hardener from edge to edge across the center of a 4" diameter puddle).
- Puddles larger than 4" (10 cm) in diameter will require additional hardener. Mix thoroughly until uniform color is achieved.

### APPLICATION:



- Apply in layers with even firm pressure.
- Do not apply all at once.

### FINISH:



- Rough shape with 40 – 80 grit (as needed)
- Sand filler with 80 grit or finer.
- Final sand repair and paint edge 180 grit.

*For best results, apply a premium Evercoat polyester putty to provide a smoother finish and reduce the amount of primer surfacer needed for a quality finish.*

### TECHNICAL

Appearance	Gray colored paste
VOC	Refer to Section 9 of the Safety Data Sheet
Relative Density	Refer to Section 9 of the Safety Data Sheet
Setting Time	3-5 minutes
Sand Time	15-20 minutes
Max. Recommended Thickness (sanded)	1/4 inch (6mm)

### SPECIFICATIONS:

**NOTE:** Properties are typical values and should not be considered as sales specifications. Physical testing performed @ -72°F (22°C) / 75% RH unless otherwise noted.

### SAFETY & HANDLING:

Read all directions and warnings prior to using Evercoat® products. Safety Data Sheets can be found online at evercoat.com.

### NOTES:

Never return mixed filler to can

Keep can closed and store in a cool dry place

**USE WITH EVERCOAT CREAM HARDENER ONLY!**