

PRODUCT: MAXIM™ SUPER FAST URETHANE ADHESIVE

PART NUMBER: 100886 250mL Cartridge 6 units/case

DESCRIPTION: Maxim™ Super Fast Urethane Adhesive is a two-component urethane repair material that provides incredible strength for bonding of brackets, clips, moldings, backing patches, repairing bumper tabs, bonding of cracked headlight buckets and lenses. This urethane material is used for non-structural repairs on fiberglass, SMC, PUR, RIM, RRIM, PP, TPO, TPE, EPDM and other automotive plastics.

FEATURES & BENEFITS:

- Easy to use: excellent gun ability
- High strength
- Excellent adhesion
- Excellent gap filling
- Repair torn weatherstrips
- Water leak repair of semi trailers
- Fast work time for bonding brackets, lenses and backing patches
- Excellent for attaching end brackets on bumper facias
- Fast cure times for attaching large moldings, emblems, etc.
- Remains flexible unlike cyanoacrylate adhesives
- Excellent shelf life unlike cyanoacrylate adhesives

PREPARATION: Wash the repair area with soap and warm water. Thoroughly dry entire repair area (i.e. compressed air, heat, etc.). Use an All-Purpose Cleaning Solvent on a clean, lint-free cloth and wipe the repair area (Wipe from the center of the repair area to the outside). Use a clean, dry cloth to wipe the area dry. Sand and taper the repair area according to recommendations. Apply Adhesion Promoter according to recommendations.

APPLICATION: Apply Fast Urethane adhesive to the repair area. Allow to dry, then sand. Apply primer surface according to paint manufacturer's recommendations.

TECHNICAL SPECIFICATIONS:

- | | |
|----------------|---|
| ▪ Appearance | Black / Opaque |
| ▪ VOC | Refer to Section 9 of the Safety Data Sheet |
| ▪ Working Time | 45-45 seconds |
| ▪ Sanding Time | 12-20 minutes |
| ▪ Full Cure | 1 hours |

NOTE: Properties are typical values and should not be considered as sales specifications. Physical testing performed @ ~72°F (22°C) / 75% RH unless otherwise noted.

SAFETY & HANDLING:

For professional use only, read all directions and warnings prior to using Evercoat® products. Keep cartridge closed and store in a cool dry place.

Safety Data Sheets can be found online at evercoat.com.



a division of Illinois Tool Works Inc. | 6600 Cornell Road | Cincinnati, OH 45242 | (513) 489-7600

©2023 Evercoat

evercoat.com

100-310-100886-TDS

4.2023